## (19) World Intellectual Property Organization International Bureau



### 

### (43) International Publication Date 27 September 2001 (27.09.2001)

### **PCT**

# (10) International Publication Number WO 01/71189 A1

(51) International Patent Classification7: 39/00

F04B 39/10,

(21) International Application Number: PCT/GB01/01240

(22) International Filing Date: 20 March 2001 (20.03.2001)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

0006978.1

22 March 2000 (22.03.2000) GB

- (71) Applicant (for all designated States except US): ARCTIC CIRCLE LIMITED [GB/GB]; Coldnose Court, Coldnose Road, Rotherwas Industrial Estate, Hereford HR2 6JL (GB).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): Lawson, Stuart [GB/GB]; 111 Bath Road, Thatcham, Berkshire RG18 3BH (GB).


- (74) Agent: JONES, Graham, Henry; Graham Jones & Company, 77 Beaconsfield Road, Blackheath, London SE3 7LG (GB).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

#### Published:

with international search report

[Continued on next page]

(54) Title: A VALVE ASSEMBLY WITH DAMPER MEANS



(57) Abstract: A valve assembly (9) cmprising a reed (11), a port (13) which is opened and closed by the reed (11), and damper means (15) for the reed (11), the damper means (15) comprising a tube which is in communication with the port (13) on a side of the port (13) remote from the reed (11), and the tube being of such a size that, in use of the valve assembly (9), the tube contains sufficient fluid to provide substantial damping for the reed (11).

The state of the s

01/71189 A1